





SE H4-24 PRO

with two power cables

Lenght	Watt	Volt
1000mm	10W	24VDC
2000mm	20W	24VDC
3000mm	30W	24VDC
6000mm	60W	24VDC



SE H4-24 PRO integrates a FREE-CUT light source that allows the module to be cut to the desired length at any point of the profile.





The luminaire is protected from water splashes from all directions, preventing these from penetrating in damaging quantities (IP44).



The indicated CCT (Correlated Colour Temperatures) refer to the average measured colour temperatures. The nominal values of the light sources are 3400 K (WW) and 5000 K (NW).



The end caps of SE H4-24 PRO are the same size as the profile allowing the entire profile to be flush panel recessed into the groove. The power cord may exit axially or radially to the installation surface.



Colour appearance	warm white	natural white
Colour temperature	3000 K	4300 K
Luminous flux	800 lm/m	1040 lm/m
Luminous efficiency	80 lm/W	104 lm/W
CRI	Ra 90	Ra 90

SE H4-24 PRO

siliconic LED micro profile



SE H4-24 PRO is a micro profile with symmetrical light projection, designed for flush panel recessed installation in a through-milling with a width of 4mm and a depth of 8mm, recommended for use on any furnishing element. The luminaire is protected from water splashes from all directions, preventing these from penetrating in damaging quantities (IP44). Developed with milky-effect diffusing silicone coating technology, it integrates a single-colour FREE-CUT LED module with 180 LEDs/m that allows it to be cut to the desired length at any point on the profile. Upon request, SE H4-24 PRO is also available in custom lengths of up to 6000mm (IP20), complete with a 2000mm power cord that can exit radially or axially to the installation surface from end caps the same size as the profile. Power supply not included, to be ordered separately.

