



# PREP P

## SURFACE PREPARATION

TECHNICAL SHEET 13/11/2023

### KEY FEATURES

- Pre-treatment for (teak)wood
- Enhances adhesion on porous substrates
- Fast Drying

### DESCRIPTION

Bostik Prep P is a pre-treatment designed to improve the adhesion of most Bostik elastic bonding products on porous surface substrates.

### APPLICATIONS

- Pre-treatment of mineral substrates (a.o. brickwork, concrete)
- Pre-treatment of wood substrates (a.o. seams in teak decks)

### METHOD OF USE

Substrates should be clean, dry, dust- and grease-free. Prep P container should be kept closed until the moment of use. Do not use Prep P directly from the original container but pour as much Prep P into a clean glass or metal container as can be used within 30 minutes and immediately close the original container firmly.

Do not return unused material to the original container. If necessary e.g. if heavily contaminated, substrates may first be cleaned with Cleaner I or Cleaner 14, allow cleaners to dry for 5 minutes before application of Prep P.

Apply Prep P in a thin layer to the surface for it to form a continuous, uninterrupted film. Do not apply Prep P on an already dried Prep P.

Best results are obtained when the bonding/sealing is realised within 6 hours after application of Prep P. Avoid contact with the cleaned, pre-treated surface, as this can lead to poor adhesion. Do not use when condensation is formed on the substrate.

### TECHNICAL DATA

CHARACTERISTIC		VALUE
Physical Form		Low viscous liquid
Colour		Light yellow/Transparent
Specific Gravity	[g/ml]	Ca. 1.1
Drying Time 20°C/50% R.H.	[min]	ca. 30
Dry Content	[%]	ca. 50
Coverage	[m <sup>2</sup> /l]	8 - 10
Flash point (Closed cup)	[°C]	ca. -4
Application Temperature	[°C]	+5 to +30
Packaging		500ml can

### STORAGE

Prep P can be stored for up to 12 months in unopened container in a dry place at temperatures between +5°C and +30°C. Once opened, Prep P can be used for a maximum of 2 weeks (container should be firmly closed when not in use).

### FURTHER INFORMATION

The following publication is available on request:  
- Material Safety Data Sheets (MSDS).

### SMART HELP

Please contact your local representative



**Bostik S.A.**  
Colombes, France  
Phone : +33 (0)1 49 00 90 00  
[www.bostik.fr](http://www.bostik.fr)

**Bostik Ltd.**  
Stafford, UK  
Phone : +44 (0) 1785 27 27 27  
[www.bostik.co.uk](http://www.bostik.co.uk)

**Bostik GmbH**  
Borgholzhausen, Germany  
Phone : +49 (0)54 25/801-0  
[www.bostik.de](http://www.bostik.de)

**Bostik B.V.**  
Oosterhout, The Netherlands  
Phone : +31 (0)162 491 000  
[www.bostik.nl](http://www.bostik.nl)