



T-type 110/90°

For wood door cabinets with blind panels



- Opening angle 110°
- Drilling diameter for hinge cup 35mm
- Drilling depth 12mm
- Hinge on plate mounting system 3Way snap-on





Technical details

	Interaxis 45mm	Interaxis 48mm
Cup type		
Item number	702-0A95-650	702-0A97-650
Item number	702-0D35-650	702-0D37-650
EasyFix	702-0D29-650	702-0D31-650

Drilling patterns for hinge cups → see page 2.17

Cranking
17mm




Cup made of steel, arm made of zinc

Mounting plates

- Cam adjustable cruciform mounting plate → see page 2.81
- Cruciform mounting plate → see page 2.83
- Cam adjustable linear mounting plate → see page 2.81
- Face frame adapter plate → see page 2.83


Hinge cup screws

If not pre-mounted



820-6328-050


10000 Pcs




Cover caps for hinge arm → see page 2.177

Hinge angle restrictor → see page 2.175

Legend of hinge cup symbols




Door adjustment




For further explanation → see pages 2.22-2.24

Mounting details




Drawing shows application on D=2mm mounting plate



Drawing shows application on D=2mm mounting plate

Mounting plate drilling distance



Soft closing system



Glissando TT
→ see page 2.189

Touch opening



PushOpen Solutions
→ see pages 2.199-2.204

Door clearance at R=1mm

For further explanation → see page 2.14



V	16	17	18	19	20	21	22	23	24	25	26
3	0.5	0.7	0.8	1	1.2	1.5	1.7	2.1	2.8	4.1	5.5
4	0.4	0.7	0.8	1	1.2	1.5	1.7	2.1	2.3	3.1	4.5
K											
5	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	3.5
6	0.4	0.6	0.7	0.9	1.1	1.4	1.6	2	2.2	2.6	2.9 F _{MIN}

Gap Z_{MIN}=0